

Wohler VIS 250 Video Inspection Camera

TECHNICAL DATA

Monitor

Dimensions housing.....7" x 4.5" x 1.3"
 TFT-display7" / 16:9 format
 Video outFBAS signal
 Weight.....1 lbs

Power Supply

Power supply.....Space for 2 rechargeable batteries, each 12 V or via power pack
 Battery operating time.....Max. 2 rechargeable batteries, each 120 mins. = 4 h (battery status in display)

Miniature color camera head, 1" diameter

Type1/3" COLOR CMOS
 Resolution420 lines
 Pixels.....768 x 576 (PAL), 656 x 492 (NTSC)
 Light sensitivity.....0.5 Lux
 Lensf = 0.09", F = 2.5
 Viewing angle.....115°
 Light source12 white LEDs
 Degree of protectionWaterproof to IP 68
 Dimensions1" dia x 1.5" long
 Weight.....0.5 lbs
 Operation temperature.....32...104 °F, RH 95 % MAX
 Storage temperature.....-4...122 °F, RH 95 % MAX
 Transmitter frequency.....8.9 kHz

Push rod

Length.....100 ft.
 Diameter.....0.24"
 Distance measurementelectronic meter counter

Plastic case

Dimensions.....20" x 17" x 7" (l x w x h)
 Weight.....15 lbs

Locator receiver

Display.....Graphic visualization of transmitted position

Output impedance

Headphones.....32 Ohm
 Power supply.....12 V NIMH battery (rechargeable)
 Operating temperature.....32...104 °F
 Storage temperature.....14...104 °F
 Weight.....1.3 lbs
 Dimensions13" x 6" x 3" (l x w x h)

Memory (Wohler VIS 250)

Recording4 GB SD card (2.5 h recording capacity)
 InterfaceMini USB port