



CircleSafe®



## CircleSafe® 800A

### Physical Characteristics

Forest green liquid, slight odor contained in an aerosol package.

### Particle Certification

Particles meet or exceed all relevant specifications including but not limited to ASTM E 1444, MIL-STD-271, NAVSEA 250-1500-1, ASTM E 709 and ASME B & PV Code -Section V, AMS 3046, AMS 3161, AMS 2641 and A-A-59230. Certification is included with each shipment.

### Particle Color

Fluorescent Yellow-Green

### Average Particle Size

3 µm

### AMS Standard

3046

### SAE Sensitivity\*

8

[\*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

### Temperature Limit

120°F Maximum

### Related Product Information:

Safety Data Sheet

Technical Bulletin 271A

### Item #

FG-3130

### Package Size

Case of 12 x 16 oz. Cans

CircleSafe® 800A is an aerosol spray can of Mi-Glow® 800 fluorescent yellow-green particles and CircleSol M™, a refined petroleum distillate. It is designed to detect very fine discontinuities found in finished products and critical, highly stressed component parts. Its ultra-bright, ultra-sensitive particles allow for excellent detection. The carbon dioxide propellant reduces combustible hazard.