

## **B200**

# **AC Contour Probe**

The B200 Contour Probe is a rugged high performance instrument designed for Magnetic Particle inspection to accepted Nondestructive testing standards.

Parker Contour Probes are designed with flexible legs that allow the field to be "focused" at a precise area of inspection. Components are protected by a reinforced glass-filled nylon housing. Model B200 and B200S produce a strong constant AC field.

Plastic carry cases (PL-Case) and Test Kits (PL-A Kit & A Kit) are available. Standard test kits include 1 lb. each of Red & Gray powder, PB1 powder blower, and carrying case.

### **Features**

- High-impact, glass-filled nylon housing
- AC Only
- Dual coil design for reduction of heat to the operators hand
- Ergonomic handle for ease of use over long periods of time
- Plastic actuator for consistent activation of the switch
- One year repair/replacement guarantee
- Exceeds ASTM lifting standards

## Standards Compliance

- ASME Section V, Article 7
- ASTM E709
- ASTM E1444
- ASTM E3024
- EN ISO 9934-3 (230V Only)
- CE (Optional 230V Only)



### **Applications**

**Defect location**: Surface

#### Ideal for:

- Field Testing
- Spot Inspections
- In-service Inspections
- Demanding Environments
- Welding Inspections

### **Defect Examples:**

- Inclusions
- Seams
- Shrink cracks
- Tears
- Laps
- Welding slags
- Grinding cracks
- Quenching cracks
- Fatigue cracks

April 2020 Page **1** of **2** 

## **Product Properties**

Weight	7 lbs. (3.18 kg)
Leg Span	0 – 12 in (0 – 304.8 mm)
Cord Length	10 ft. (3.048 m)
Duty Cycle	50%
Electrical Requirements	115VAC - 50/60 Hz : 3 Amps 230VAC - 50/60 Hz : 2 Amps

# **Use Recommendations**

NDT Method	Magnetic Particle Testing
Recommended	Weight Lift Test Bar – TB10
Accessories	Yoke Light – Y200

### Part Numbers

B200 - 115VAC

B200S - 230VAC