

# RiMaxio

High pressure-jet camera for cleaning and inspections from DN 50 – DN 150 ( ID 2.0" – ID 6" )  
45° bendable from DN 50 ( ID 2.0" ) ( art-no. 88083 )

with the following equipment:

- **System**
  - 20 m ( 60 ft. ) high pressure hose DN 8 ( ID 0.3" )
  - 40 m ( 130 ft. ) camera cable
  - Front camera with steerable high pressure nozzle
  - Forward fired nozzle DN 8 ( ID 0.3" ) with changing use
- **Handling**
  - simply carrying via different grip possibilities ( lateral, in front of the breast, etc. )
  - lifting in pairs ( onto a scaffold for example )
  - passing to another person ( into a trench for example )
- **Stability**
  - all-round protection by circular cage
  - Composition of sturdy stainless steel, high-quality synthetic material and lightweight aluminium for a perfect relation between stability and weight
  - industry-mounted reel bracket
  - stable stand by large footprints
  - splash water protected
- **Display**
  - display ( optional ) turnable in all directions
- **Brake**
  - high grade wheel disc brake
  - rapid choice with grip " Firm Dragging-Loose " ( fine adjustable via twist-part on the grip )
- **Meeter counter**
  - high precision meeter counter with displaying in the monitor
  - set of meters on / off with buttons control
  - minimum of movable elements
- **Service**
  - service pleasant by numerous plug connections and modular structure
  - easy packaging and transporting because of cubical form
- **Other**
  - bag for small parts



options:

	Name	article	art-no.	price
1	TFT-monitor, 5.6" • adjustable holder on reel • robust metal – housing with sun shield		20170	
2	TFT – Monitor 5.6" with SD – card memory • adjustable holder on reel • robust metal – housing with sun shield • SD-memory card-slot for saving of single pictures or video sequences • SD-card 4 GB ( up to max. 32 GB upgrade possible ) • easy handling with integrated buttons		20171	
3	TFT – Monitor 8" with SD – card memory • high resolution • adjustable holder on reel • robust metal – housing with sun shield • SD-memory card-slot for saving of single pictures or video sequences • SD-card 4 GB ( up to max. 32 GB upgrade possible )		20172	



		article	art.no.	price
4	<ul style="list-style-type: none"> <li>• Transmitter circuit board built in reel</li> <li>• sonde mounted in camera head</li> </ul>		80194	
5	<ul style="list-style-type: none"> <li>• f 517 Hz</li> <li>• Local side</li> <li>• Transmitter circuit board built in reel (€ 235,00)</li> <li>• sonde mounted in camera head (€ 400,00)</li> <li>• f 33 KHz</li> </ul>		88063	
6	Remote control		79015	
7	Accumulator 36V / 2.6 Ah incl. recharger - accumulator developed especially for the needs of the Rtec construction - lithium ion technique - made in Germany - quick-change mount for the reel-frame - sturdy housing - sturdy and comfortable electric plug connection - test button for lead-in status		98107	
8	Accumulator 24V / 2.6 Ah		80187	
9	Brace for accumulator		98097	
10	Upgrade kit for the reel frame and for T-201e		10336	
11	Upgrade kit for COM-100 and COM-100e using HD Hose		10338	
12	HD Hose DN 8 (ID 0.3" / 7.20 in / 180 ft.) (included in Basic delivery)		53812	
13	Forward feed nozzle DN 8 (ID 0.3") with changing use (included in basic delivery)		88174	
14	HD Hose DN 6 (ID 0.2" / 5.08 in / 68 ft.)		98139	
15	Forward feed nozzle DN 6 (ID 0.2") with changing use		88064	
16	guide ball from DN 100 (ID 4")		88212	

